### Veeam Straight Disk vs. Deduplication Appliance

DATA SHEET



deduplication appliances will cost far less due to greater deduplication ratios. They use far less disk than using straight disk. The role of deduplication is to store only unique bytes or blocks called changed data versus storing all of the data.

With ExaGrid disk-based backup appliances, backups are written directly to a disk landing zone, avoiding inline processing, ensuring the highest possible backup performance resulting in the shortest backup window. Adaptive deduplication performs deduplication and replication in parallel with backups while providing full system resources to the backups for the shortest backup window.







Hyper-converged Backup and Recovery/



Storage Magazine Names ExaGrid "Product of the Year. Backup & DR Hardware Finalist – 2017"

### Veeam – Straight Disk vs. Deduplication Appliance

Virtualized backup applications have many unique features and functions that require the full VM to be available and ready to be booted in seconds to minutes.

- The ability to boot a VM from the backup storage system when the primary VM environment is offline The ability to perform audits or Sure Backups to prove to an internal or external audit team that VMs can be booted or restored in the case of a failure
- The ability to create a synthetic full on a regular basis in order to ensure reliable full backup restores; integration of the Veeam Accelerated Data Mover with ExaGrid's landing zone provides synthetic fulls that are 6X faster
- VM boots on the backup system to test patch, configuration, and other updates before rolling out to the production environment
- Support of Veeam's Scale-Out Backup Repository (SOBR)

# Fastest Backups for the Shortest Backup Window

ExaGrid understands that data deduplication is highly compute intensive and should not be performed during the backup window as the deduplication will slow down ingest performance and, as a result, will lengthen the backup window. ExaGrid provides a unique disk landing zone in each appliance where backups are written directly to disk so that the compute-intensive data deduplication process doesn't impact ingest. This approach provides the fastest backup ingest rate of any other deduplication solution. ExaGrid uses "adaptive" deduplication to deduplicate and replicate data to the disaster recovery (DR) site during the backup window (in parallel with the backups) but not inline between the backup application and the disk. This unique combination of a landing zone with adaptive deduplication provides for the fastest backup performance, resulting in the shortest backup window as well as a strong disaster recovery point (RPO).

## Fastest Restores, VM Boots, and Offsite Tape Copies

Ninety-five percent or more of the total volume of restores, VM boots, and offsite tape copies come from the most recent backup, so keeping the most the most recent backup in only deduplicated form will require a compute-intensive, timeconsuming data "rehydration" process that will slow down restore requests. VM boots can take hours from deduplicated data. Since ExaGrid writes directly to the disk landing zone, the most recent backups are kept in their full undeduplicated, native form. All restores, VM boots, and offsite tape copies are fast as the overhead of the data rehydration process is avoided. As an example, ExaGrid can provide the data for a VM boot in seconds to single-digit minutes versus hours for inline data deduplication backup storage appliances that only store deduplicated data. ExaGrid maintains all long-term retention (weeks, months, years) in a deduplicated format for storage efficiency.

ExaGrid provides the best of both worlds – writing to ExaGrid's disk landing zone delivers the fast ingest and restore performance of straight disk while also leveraging the cost savings gained with long-term deduplicated storage. ExaGrid is the only deduplication solution with these combined benefits in a single product.

#### **Fixed-Length Backup Window**

Since data deduplication uses a lot of processor and memory resources, as data grows, the amount of data deduplication to be performed grows as well. The first generation of deduplication storage appliances utilize a "scale-up" storage approach with a fixed resource front-end controller and disk shelves. As data grows, they only add storage capacity. Because the compute, processor, and memory are all fixed, as data grows, so does the time it takes to deduplicate the growing data until the backup window is so long that the front-end controller has to be upgraded (called a "forklift" upgrade) to a larger/faster controller which is disruptive and costly. ExaGrid provides full appliances in a scale-out system. Each appliance has landing zone storage, deduplicated repository storage, processor, memory, and network ports. As data volumes double, triple, etc., ExaGrid doubles, triples, etc. all required resources to maintain a fixed-length backup window. If the backups are six hours at 100TB, they are six hours at 300TB, 500TB, 800TB, etc. Expensive forklift upgrades are avoided, and the aggravation of chasing a growing backup window is eliminated.

United States:2000 West Park Drive | Westborough, MA 01581 | (800) 868-6985United Kingdom:200 Brook Drive | Green Park, Reading, Berkshire RG2 6UB | +44 (0) 1189 497 051Singapore :1 Raffles Place, #20-61 | One Raffles Place Tower 2 | 048616 | +65 6808 5574



ExaGrid reserves the right to change specifications or other product information without notice. ExaGrid and the ExaGrid logo are trademarks of ExaGrid Systems, Inc. All other trademarks are the property of their respective holders. ©2018 ExaGrid Systems, Inc. All rights reserved.

#### **Disk-Based Backup with Data Deduplication Comparison**

Feature	<b>ExaGrid</b> Adaptive deduplication Scale-out architecture Landing zone	Dell EMC Data Domain, HPE, Quantum Inline deduplication Scale-up architecture
Backup Performance	<b>FASTEST</b> Data writes direct to disk; as data grows, additional storage and bandwidth are added.	<b>ADEQUATE</b> Deduplication is compute intensive and occurs during the backup, resulting in slower backups.
Fixed-Length Backup Window	<b>YES</b> As data grows, additional processor, memory, and bandwidth are added.	<b>NO</b> Uses a fixed resource front-end controller and only disk is added as data grows.
Fast Restores	<b>YES</b> Most recent data resides in full, undeduplicated format in a landing zone for fast restores.	<b>NO</b> All data is deduplicated and has to be rehydrated before a restore can be performed.
Fast Offsite Tape Copies	<b>YES</b> Most recent data resides in a full, undeduplicated format in a landing zone for fast offsite tape copies.	<b>NO</b> All data is deduplicated and has to be rehydrated before an offsite tape copy can be made.
Instant VM Recoveries vMotion into Production	<b>YES</b> Most recent VMs are in a complete, undeduplicated format in the landing zone and can be immediately booted and used while migrated to production storage.	<b>NO</b> All data is deduplicated and has to be rehydrated both during VM booting, which can take hours for production-sized VMs, and completely rehydrated during migration to production storage.
Accelerated Synthetic Full	<b>YES</b> ExaGrid-Veeam Accelerated Data Mover allows the entire synthetic full operation to occur on the ExaGrid appliance. Most recent VMs are stored in a complete, undeduplicated format in the landing zone and the Veeam Data Mover can easily reconstitute a synthetic full in the ExaGrid landing zone.	<b>NO</b> The Veeam Data Mover does not run on inline deduplication appliances.
Veeam vPower features such as - SureBackup - Virtual Lab - U-AIR	<b>YES</b> Most recent VMs are in a complete, undeduplicated format in the landing zone and can be immediately booted and used for Veeam vPower operations.	<b>NO</b> All data is deduplicated and has to be rehydrated both during VM booting (which can take hours for production-sized VMs) and completely rehydrated during all Veeam vPower operations.
Low Cost Scalability as Data Grows	<b>YES</b> Scale-out architecture; full server appliances are added into a single system as data grows, adding compute with capacity.	<b>NO</b> As data grows, the front-end controller falls behind and must be replaced with a bigger/faster front-end controller.
Rack Space	Average 2U per appliance	Average 3U per appliance
Power and Cooling	Average - Uses more disk but cooler, lower clock speed processors	Average - Uses less disk but very hot, higher clock speed processors
Price	Market leading	Depends on the vendor – some are market leading and some are overpriced

United States:2000 West Park Drive | Westborough, MA 01581 | (800) 868-6985United Kingdom:200 Brook Drive | Green Park, Reading, Berkshire RG2 6UB | +44 (0) 1189 497 051Singapore :1 Raffles Place, #20-61 | One Raffles Place Tower 2 | 048616 | +65 6808 5574



www.exagrid.com

ExaGrid reserves the right to change specifications or other product information without notice. ExaGrid and the ExaGrid logo are trademarks of ExaGrid Systems, Inc. All other trademarks are the property of their respective holders. ©2018 ExaGrid Systems, Inc. All rights reserved.